
Orbix 3.3 Service Pack 9 Core Services

Release Notes

July 2007

Contents

Introduction	2
Orbix 3.3 SP 9 Core Services C++ Edition	5
Orbix 3.3 SP 9 Core Services Java Edition	7
OrbixNames 3.3 SP 9	9
Orbix SSL C++ 3.3 SP 9	10
Orbix SSL Java 3.3 SP 9	12
Appendix	14

Introduction

Orbix 3.3 SP 9 Core Services is a service pack release of Orbix 3.3 on Red Hat Enterprise Linux 3, Windows XP Professional x64, Windows 2003 Server, AIX 5.2 and 5.3, Compaq Tru64, and Solaris 2.8 and 10. It supports Orbix Java edition, Orbix C++ edition and OrbixNames. This document contains information about Orbix 3.3 SP 9, including build information, details of bugs that have been fixed in this release, known problems and workarounds, new features, tips, and deprecated features.

Orbix 3.3 SP 9 and Orbix 3.0.1

For details of the changes that took place between Orbix 3.0.1 and Orbix 3.3, see the Orbix 3.3 Release Notes at <http://www.iona.com/docs> under the heading Orbix Generation 3.

There have been no changes to the APIs since Orbix 3.3.

Migrating from an Earlier Version of Orbix

For information on migrating from an earlier version of Orbix to Orbix 3.3 SP 9, see the Migration Guide at: www.iona.com/products/MigrationGuide.pdf.

Interoperability with Other IONA Products

The Java and C++ editions of Orbix 3.3 SP 9 have been tested with, and are interoperable with, each other except for those areas that are documented under known problems.

The Java and C++ editions of Orbix 3.3 SP 9 have also been tested with, and are interoperable with, the following Orbix products:

- Orbix 3.3 SP 8 C++ and Java editions.
- Orbix 3.3 SP 7 C++ and Java editions.
- Orbix 3.3 SP 6 C++ and Java editions.
- Orbix 3.3 SP 5 C++ and Java editions.
- Orbix 3.3.4 C++ and Java editions.
- Orbix 3.3.3 C++ and Java editions.
- Orbix 3.3.2 C++ and Java editions.
- Orbix 3.3.1 C++ and Java editions.
- Orbix 3.3 C++ and Java editions.
- Orbix E2A Application Server Platform 6.0 SP3 C++ and Java.
- Orbix Trader 1.2.1 Java edition (no C++ edition available).
- Orbacus 4.0.5.

- Orbix 3.0.l
- OrbixWeb 3.2

Licensing

- The IDL compilers, `idl` and `idlj`, are licensed.
- The Orbix daemon `orbixd` is licensed.

Deprecated Features Policy

When a feature is deprecated it means that:

- No support for this feature is given for the current version and for subsequent versions (that is, we do not explain how to use it and we do not fix any bugs in this feature).
- If you have not used this feature before, DO NOT start using it with this release.
- If you are already using this feature then you should remove it if at all possible.
- The feature may not be present in future versions of the product.

Documentation Errata

The following is a list of errors in the Orbix 3.3 documentation errors. If you find an error in the documentation please email docs-support@iona.com for prompt confirmation.

- The `CORBA::ORB::connectionTimeout()` is in milliseconds and not in seconds as stated in the *Orbix Programmer's Reference, C++ Edition*.

Development Environments

For details of the operating system versions and compiler versions on which Orbix 3.3 SP 9 is built and certified, see the following link:

http://www.iona.com/products/orbix/orbix_platforms.htm

Note: You may build and run an Orbix 3.3 SP 9 application on any of the platforms listed for Orbix 3.3 in the preceding link.

NOTES to all elements/services that use Java

The following subsections contain information that is relevant for all elements/services that use Java.

JRE not included

The Orbix 3.3 SP 9 installer does not include a Java Runtime Environment (JRE).

New environment variable

A new environment variable, `JAVA_P_FLAG`, was introduced in Orbix 3.3 SP 7. The purpose of this flag is to accommodate Orbix 3.3 Java's ORB classes implementation to take precedence over Sun's, while running Orbix 3.3 Java applications using JDK 1.4. This flag is also applicable for JDK 5.0.

The Orbix 3.3 SP 9 installer automatically sets the value of this variable based on the selected JDK version. It sets the variable to `/p` for JDK 1.4 and JDK 5.0 and leaves it blank for other JDK versions.

Once Orbix 3.3 SP 9 is installed, this variable is available in the environment script, `setenv.sh`, so that it is set in the Orbix environment.

For more details, read the following Knowledge Base articles:

- [What is JAVA_P_FLAG for and how is it used in Orbix 3.](#)
- [Why my existing IDL does not compile while using JDK 1.4.x.](#)
- [Why am I getting org.omg.CORBA.NO_IMPLEMENT or org.omg.CORBA.NO_PERMISSION exception while using JDK 1.4.x?](#)

Orbix 3.3 SP 9 Core Services C++ Edition

This section describes changes made to the Orbix 3.3 SP 8 C++ edition for the Orbix 3.3 SP 9 C++ edition.

New Features

Orbix 3.3 SP 9 C++ edition is binary compatible with Orbix 3.3 C++ edition. Orbix is no longer limited to 1024 simultaneous connections on UNIX systems,

New and Modified APIs

No existing APIs have been modified. The following new APIs have been added:

- CORBA::BOA::getFileDescriptors(int*& fdSet)
- CORBA::ORB::getAllOrbixFDs(int*& fdSet)
- CORBA::ORB::getForeignFDSet(int*& fdSet)
- CORBA::ORB::getSelectableFDSet(int*& fdSet)

See the *Orbix Reference Guide C++ Edition* for more details.

Functionality Removed

Orbix 3.3 SP 9 C++ edition is binary compatible with Orbix 3.3 C++ edition. No functionality has been removed.

Deprecated Features

The following is a list of deprecated features in Orbix C++ edition:

Feature	Description	Feature Removed	When Deprecated
<code>_bind()</code>	Should use other means.	No	Orbix 3.0
Transformers	Can use SSL for security.	No	Orbix 3.0
Piggy Backing Data with Filters	Should use Service Contexts.	No	Orbix 3.0
Opaque Data Type		No	Orbix 3.0
Orbix Network Protocol (POOP)	Must use IIOP instead.	No	Orbix 3.0
IDL Compiler options <code>-i</code> and <code>-f</code>		No	Orbix 3.0
IR	Replaced with the IFR.	Yes	Orbix 3.0
Locator	Can implement own load balancing solution.	Yes	Orbix 3.3

Orbix 3.3 SP 9 Core Services Release Notes

Non Native Exceptions	Must use Native Exceptions	Yes	Orbix 3.3
TIE macro DEF_TIE(l,X)	Use other form	Yes	Orbix 3.3
Configuration Explorer ConfigurationExplorer.bat	Allows you to configure Orbix components without modifying the configuration files directly.	No	Orbix 3.3 SP 5
Server Manager ServerManager.bat	Allows you to manage the Implementation Repository.	No	Orbix 3.3 SP 5

Note: Orbix 3.0 was released February 1999 and Orbix 3.3 was released September 2000.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 9 C++ edition:

Incident ID	Synopsis
70241	Increase the value for the fd_setsize variable on Solaris.
70362	Orbix 3.3 client fails to bind to an Orbix 3.3 server (with bidirectional IIOp enabled) when the server's IOR is resolved from an Orbix 6.x Naming Service.
70656	Introduce a flag to enable the Orbix 3.3 compiler to behave as in version 3.0.1 with the ability to generate support code in the .cxx files for user defined types.
70726	Orbix daemon 3.3.8 memory leak.
70892	A server that has had no client calls after 50 days suddenly starts to consume 100% of CPU usage.
70893	Timeout on the network thread select() call is observed to be approximately 50 days.
70927	Orbix 3 client hangs when constantly sending signals to it.
71264	IFR memory leak if multiple clients connect to and query the IFR continuously.

Orbix 3.3 SP 9 Core Services Java Edition

This section describes changes made to the Orbix 3.3 SP 8 Java edition for the Orbix 3.3 SP 9 Java edition.

New Features

Orbix 3.3 SP 9 Java edition is binary compatible with Orbix 3.3 Java edition. No existing features were modified.

The following new feature has been added:

A callback port can now be specified through the following new configuration variables:

- OrbixWeb.IT_CALLBACK_PORT_BASE
- Orbix.Web.IT_CALLBACK_PORT_RANGE

These configuration variables specify the first port to be assigned and the number of ports starting at this port number to assign (for example, a base of 5000 and range of 2 allocates 5000 and 5001 for the callbacks). If another client tries to connect with base and range after these two ports are assigned, an exception about setting the range to a larger size will be thrown, and the specified will quit.

These configuration variables can be specified in any of the following ways:

- In the configuraton file (OrbixWeb3.cfg).
- Programatically through the code. For example:

```
IE.Iona.OrbixWeb._CORBA..Orbix.SetConfigItem("OrbixWeb.IT_CALLBACK_PO  
RT_BASE", "5000");  
IE.Iona.OrbixWeb._CORBA..Orbix.SetConfigItem("OrbixWeb.IT_CALLBACK_PO  
RT_RANGE", "10");
```
- By passing them as system properties to the VM when running the client. For example:

```
-DorbixWeb.IT_CALLBACK_PORT_BASE=5000  
-DorbixWeb.IT_CALLBACK_PORT_RANGE=10
```

New and Modified APIs

Orbix 3.3 SP 9 Java edition is binary compatible with Orbix 3.3 Java edition. No new APIs were added and no existing APIs were modified.

Functionality Removed

Orbix 3.3 SP 9 Java edition is binary compatible with Orbix 3.3 Java edition. No functionality has been removed.

Deprecated Features

The following is a list of features deprecated in Orbix Java edition:

Feature	Description	Feature Removed	When Deprecated
_bind()	Should use other means.	No	OrbixWeb 3.2
Transformers	Can use SSL for security.	No	OrbixWeb 3.2
Piggy Backing Data with Filters	Should use Service Contexts.	No	OrbixWeb 3.2
Opaque Data Type		No	OrbixWeb 3.2
Orbix Network Protocol (POOP)	Must use IIOP instead.	No	OrbixWeb 3.2
IDL Compiler options <code>-i</code> and <code>-f</code>		No	OrbixWeb 3.2
Orbix Java Activator (Orbixdj.bat)	Java Activator in Graphical mode	No	Orbix 3.3 SP 5

Note: OrbixWeb 3.2 was released February 1999.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 9 Java edition:

Incident ID	Synopsis
70838	OrbixWeb could not close connections to clients unplugged from the network.
70957	Client want to specify a port for callbacks using the OrbixJava daemon.
B771182	Orbix C++ replies with a fragmented message when it is sent a fragmented message regardless of the setting for IT_SEND_FRAGMENTS.
70318	Verbose log message cannot be suppressed.
70379	Verbose log message cannot be suppressed.

OrbixNames 3.3 SP 9

This section describes changes made to OrbixNames 3.3 SP 8 for OrbixNames 3.3 SP 9.

New Features

OrbixNames 3.3 SP 9 is binary compatible with OrbixNames 3.3. No new features have been added and no existing features have been modified.

New and Modified APIs

OrbixNames 3.3 SP 9 is binary compatible with OrbixNames 3.3. No new APIs have been added and no existing APIs have been modified.

Functionality Removed

No functionality has been removed.

Bugs Fixed

No bugs were fixed in Orbix Names 3.3 SP 9.

Deprecated Features

The following is a list of features deprecated in OrbixNames:

Feature	Description	Feature Removed	When Deprecated
Names Service browser NamesBrowser.bat	Allow you to monitor and manage the Naming Service externally to your applications.	No	Orbix 3.3 SP 5

Known Problems

The Orbix Naming Service will be unable to obtain its SSL private key passphrase from the KDM when running in secure mode within a 64-bit Java Virtual Machine on AIX operating systems.

Orbix SSL C++ 3.3 SP 9

This section describes changes made to OrbixSSL C++ 3.3 SP 8 for OrbixSSL C++ 3.3 SP 9.

New Features

OrbixSSL C++ 3.3 SP 9 is binary compatible with OrbixSSL C++ 3.3 therefore no new APIs have been added nor existing ones modified.

New and Modified APIs

OrbixSSL C++ 3.3 SP 9 is binary compatible with OrbixSSL C++ 3.3 therefore no new APIs have been added nor existing ones modified.

Functionality Removed

OrbixSSL C++ 3.3 SP 9 is binary compatible with OrbixSSL C++ 3.3, therefore no functionality has been removed.

Credit Attribution

- I. The bundled OpenSSL command line utility and toolkit includes software written by Eric A. Young (eay@cryptsoft.com). The version of openssl used is 0.9.8c. The cryptographic libraries used by OrbixSSL C++ were also written by Eric A. Young. For more details on OpenSSL please see the OpenSSL website at www.openssl.org.

Bugs Fixed

This section describes the bugs fixed in this release. All bugs are described in terms of the following:

- Incident ID
This is the reference number used by the development teams to track bugs, which may in turn relate to one or more problem reports (PR) as reported by customers.
- Synopsis
This is a short description of the reported problem. A description of the fix is included where necessary.

The following bugs were fixed in Orbix 3.3 SP 9 Java edition:

Incident ID	Synopsis
71342	OrbixSSL 3.3.8 does not honor IT_SPECIFIED_SECURE_CONNECT.

Known Problems

The installer does not automatically update the 64-bit ssl libraries with the default location of the Orbix SSL configuration file.

Orbix SSL Java 3.3 SP 9

This section describes changes made to OrbixSSL Java 3.3 SP 8 for OrbixSSL Java 3.3 SP 9.

New Features

OrbixSSL Java 3.3 SP 9 is binary compatible with OrbixSSL Java 3.3 therefore no new APIs have been added nor existing ones modified.

No new features have been added in this release.

New and Modified APIs

OrbixSSL Java 3.3 SP 9 is binary compatible with OrbixSSL Java 3.3 therefore no new APIs have been added nor existing ones modified.

Functionality Removed

OrbixSSL Java 3.3 SP 9 is binary compatible with OrbixSSL Java 3.3, therefore no functionality has been removed.

Deprecated Features

The following is a list of features deprecated in OrbixNames:

Feature	Description	Feature Removed	When Deprecated
RC2 Cipher Suite	JCP toolkit	YES	Orbix 3.3
JPK File Support	JPK file support for loading private keys in OrbixSSL Java. <code>keyenc</code> utility stays there for converting OrbixSSL private keys.	NO	Orbix 3.3.1

Bugs Fixed

There are no bug fixes in OrbixSSL Java 3.3 SP 9.

Credit Attribution

1. The bundled OpenSSL command line utility and toolkit includes software written by Eric A. Young (eyay@cryptsoft.com). The version of openssl used is 0.9.8c. The cryptographic libraries used by OrbixSSL C++ were also written by Eric A. Young. For more details on OpenSSL please see the OpenSSL website at www.openssl.org.
2. OrbixSSL Java uses the JSSL/Jcrypto 2.0 toolkit as its backend SSL engine. The cryptographic libraries used by OrbixSSL Java were written by Baltimore Technologies. For more details on the cryptographic libraries used by OrbixSSL Java see the Baltimore Technologies website at <http://www.baltimore.com/>.

Appendix

This appendix contains information that is relevant to all versions of Orbix 3.3. It does not contain information that is relevant to only one version of Orbix 3.3. It contains information about performance tips, known problems and workarounds, enhancements and new features to Orbix 3.3, but not introduced in this version. It does not contain any information about bug fixes (please refer to previous release notes for these).

This appendix contains the following sections:

- Orbix C++ Edition
- Orbix Java Edition
- OrbixNames

Orbix C++ Edition

This section describes changes made to Orbix generation 3 C++ edition products between Orbix 3.3 and Orbix 3.3 SP 8, which are relevant to Orbix 3.3 SP 9 C++ edition.

IFR Refactoring

Some refactoring of the IFR implementation was carried out in Orbix 3.3 SP 5 that affects repository storage. These changes affect the internal representation of the IFR repository. With new IFR it is possible to continue using the existing IFR repository, however, if you start using the new IFR and need to revert back to the older versions (that is pre 3.3 SP 4) the IFR repository needs to be depopulated up and repopulated using the original IDL files or a backup of the old repository. IONA recommended that you backup your IFR repository before installing any service pack after Orbix 3.3 SP 5.

Tips

Use of IT_MASK_SIGTERM, IT_MASK_SIGQUIT and IT_MASK_SIGINT

In regard to the use of configuration variables IT_MASK_SIGTERM, IT_MASK_SIGQUIT, IT_MASK_SIGINT to mask the asynchronous signals (SIGTERM, SIGQUIT, SIGINT) and IT_MASK_SIGUSR1, IT_MASK_SIGUSR2 to mask the user signals (SIGUSR1, SIGUSR2) in Orbix internal threads, do not use the method `setConfigValue()` to set these variables.

You need to export these variables as follows before you start your application:

```
export IT_MASK_SIGTERM=YES
export IT_MASK_SIGQUIT=YES
export IT_MASK_SIGINT=YES
export IT_MASK_SIGUSR1=YES
export IT_MASK_SIGUSR2=YES
```

Known Problems

This section summarizes known issues and suggested workarounds for earlier Orbix 3.3 releases.

Incident ID	Synopsis
64992	There is a known problem with foreign FDs (File Descriptors) on HPUX 11. When Orbix is asked to manage foreign FDs, there are some situations where the process hangs. It is not typical to ask Orbix to manage foreign FDs, and this problem can be avoided by not asking Orbix to manage foreign FDs.
64991	There is a known problem using C++ keywords in various situations in the IDL file. Using C++ keywords for attribute names, operations names

	and field names (of structures and exceptions) works. However, using C++ keywords as the type name of a module, interface, exception, or struct does not work. Customers should avoid using C++ keywords in the IDL as the type names of modules, interfaces, exceptions, and structs.
56121	The IDL compiler issues warnings if the IDL contains identifiers that are reserved keywords but not all lower case. For example, the IDL "interface Attribute{};" causes the warning "Warning : identifier Attribute clashes with keyword" even though it is a valid interface name and is case-different from the reserved keyword "attribute".
55600	No overloaded output-streaming operator (<<) is provided for the unsigned long long CORBA type (CORBA::ULongLong) in Orbix 3.3.
55599	No overloaded output-streaming operator (<<) is provided for the signed long long CORBA type (CORBA::LongLong) in Orbix 3.3.
55547	Orbix 3.3 generated IDL stub code on Windows NT for multi-dimensional arrays as in parameters should work around known VC6 multidimensional array const bug.
56334	When service context handlers in Orbix runtime encounter an abnormal condition, the diagnostic messages are not very informative.

Compilation problems on Windows NT result in the following error message:

"Warning: Orbix wants an fd_set of size 1024 or greater. Please include CORBA.h before winsock2.h"

This may be resolved by defining WIN32_LEAN_AND_MEAN when compiling.

For example: CL /c ... -DWIN32_LEAN_AND_MEAN ... myFile.cpp

If you do not wish to use this option when compiling you may also resolve the problem by editing CORBA.h by moving line 22,

```
#include <corba/PreCORBA.h>
```

to the position immediately after line 15,

```
#define CORBA_INCLUDES
```

Stopping double deletion of CORBA::Any when un-marshaling CORBA::Anys during DSI invocation processing

Some applications use the following pattern for memory management of CORBA::Anys required for DSI request processing. This is incorrect and causes a memory corruption error with this version of Orbix:

```
CORBA::NVList_ptr pArgList;
if (CORBA::Orbix.create_list(1, pArgList))
{
    CORBA::Short value_of_n = 0;
    // create an any on heap. This is the representative
    // of the in argument. All of the arguments (anys)
    // will be stored in an NV list
    //
    CORBA::Any* pAny = new CORBA::Any(CORBA::_tc_short,
        &value_of_n, 0);
```

```
// populate the NV list with the heap allocated any
// and name of "n"
//
pArgList->add_value("n", *pany, CORBA::DSI_ARG_IN);
// read all the arguments (values) from the request
// into the NV list
//
rSrvReq.params(pArgList);
// do invocation processing
// ***** NOTE *****
// Deleting the CORBA::Any is an error as the Orbix
// runtime will do so.
//
delete pAny; // Error! Don't do this.
}
```

This code would not have caused problems prior to Orbix 3.3.1 as Orbix 3.3 and earlier versions did not properly delete the `Any`. Since Orbix 3.3.1, Orbix deletes the `Anys`, so it is no longer necessary to do it.

Deploying an Orbix 3.3 SP 9 Daemon in Orbix 3.0.1 Environment

An Orbix 3.3 SP 9 daemon can launch Orbix 3.0.1 servers. For all Orbix 3.0.1 daemon utilities, your clients and servers work with the Orbix 3.3 SP 9 daemon. All you need to do is append the Library Path in the environment with the Orbix 3.3 SP 9 library path.

Orbix Java Edition

This section describes changes made to Orbix generation 3 Java edition products between Orbix 3.3 and Orbix 3.3 SP 8 that are relevant to Orbix 3.3 SP 9 Java edition.

Implemented APIs

The following APIs have been implemented:

Class	IE.Iona.OrbixWeb.CORBA.Any
Method	public void insert_fixed (java.math.BigDecimal d, org.omg.CORBA.TypeCode type)
Description	Takes one <code>java.math.BigDecimal</code> value along with TypeCode information, which includes scale and digits information.
Class	IE.Iona.OrbixWeb.CORBA.Any
Method	Public void insert_fixed (java.math.BigDecimal d)
Description	Takes one <code>java.math.BigDecimal</code> value without any typecode information
Class	IE.Iona.OrbixWeb.CORBA.Any
Method	Public java.math.BigDecimal extract_fixed() throws BAD_OPERATION
Description	Extracts fixed type data from Any and return a <code>java.math.BigDecimal</code> value.

Tips

Using the IDLJ compiler with JDK 1.4.x

The javac compiler, since JDK 1.4.0, is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The code generated by default by the IDLJ compiler contains import statements without a namespace or a package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with javac. Therefore, when you are using JDK 1.4, you need to supply "-jP <packagename>" to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following IONA Knowledge Base article:

[Why my existing IDL does not compile while using JDK 1.4.x.](#)

CORBA Fixed-Point Data Type Support

The CORBA fixed-point data type is fully supported in this edition. It is possible, in this edition, to use fixed type variables in arrays, structures, sequences, unions, and other

user-defined data types.

Support for Multiple Profiled IORs

In Orbix 3.3.4 the Client ORB iterates over a multi-profiled IOR until it is able to establish a connection to a server. It always starts at the first profile when connecting or reconnecting to a server.

This new feature enables interoperability with Orbix 2000 servers that utilize high availability features (these features are detailed in the Orbix 2000 2.0 install guide).

Known Problems

This section summarizes known issues and suggested workarounds in earlier Orbix 3.3 Java edition.

Incident ID	Synopsis
65605	The Server Manager GUI doesn't update when a server is started and then stopped (affects Orbix 3.3.2 and upwards). This GUI is deprecated.
64957	Fragmentation error occurs on the client side if large chunk of data is sent in fragments from an ASP 5.x and higher server. The Fragments received from the ASP server are malformed. This is interoperability issue between ASP and Orbix Java 3.3 SP 5.

OrbixNames Fails to Launch Automatically on Windows NT

If you register the Naming Service with spaces in its `bootclasspath` variable in one of the following files, the OrbixNames server fails to be automatically launched by the daemon.

```
<IONA installation directory>\bin\registerns12.bat
```

(Automatic launch should occur when you run one of the utilities for OrbixNames, `lsns` for example, or when you run a client or server that tries to use the Naming Service.)

An error like this appears in the window for the Orbix Java daemon (`orbixdj`):

```
Can't find class java.lang.NoClassDefFoundError.
```

Solution

If you find the directory name "Program Files" in these files, replace every occurrence with `progra~1`:

```
<IONA installation directory>\bin\registerns12.bat
```

The above batch files are for registering the OrbixNames server with the daemon. If you have already registered the OrbixNames server, you can undo this and register it again as follows. (Ensure that the daemon is running first of all.)

To undo the registration:

```
rmit NS
registerns12
```

Multiple “font not found” messages starting JDK 1.3.1

When Server Manager and Configuration Explorer are launched, you get multiple `font not found` messages. The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed:

```
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-  
medium-r-normal--*-%d--*-p--sun-fontspecific]
```

Workaround

1. Customize the `font.properties` file for each machine.
2. Install the `SUNIWof` font packages.

OrbixNames

This section describes changes made to Orbix generation 3 Names products between Orbix 3.3 and Orbix 3.3 SP 8 that are relevant to Orbix 3.3 SP 9 Names.

Features

IT_NAMES_REP_CLEAN_CNT Configuration Variable added to orbixnames3.cfg

The configuration variable, `IT_NAMES_REP_CLEAN_CNT`, has been added to `orbixnames3.cfg`. This variable is used to remove deleted contexts from the configuration repository.

The default value for the new variable is set to 100, which means that after deleting 100 contexts the naming repository is cleared.

In previous versions of Orbix 3.3 the naming repository was cleared every time a context was deleted which slowed down the performance of the Naming Service.

Tips

Using the IDLJ compiler with JDK 1.4.x

The `javac` compiler, since JDK 1.4.0, is more strict than previous versions and rejects import statements that import a type from the unnamed namespace. The code generated by default by the IDLJ compiler contains import statements without a namespace or a package name if your IDL contains any data definition in global scope, and the generated code results in errors while compiling with `javac`. Therefore, when you are using JDK 1.4, you need to supply `"-jP <packagename>"` to the IDLJ compiler. By doing this, the generated code comes under the given package name and compiles without any problems.

For more details, read the following IONA Knowledge Base article:

[Why my existing IDL does not compile while using JDK 1.4.x.](#)

Known Problems

Note: The bug IDs 4276129 and 4285197 refer to JDK bugs and are not assigned by IONA.

Bug ID: 4276129 in JDK1.3.1 - Multiple font not found messages starting jdk1.3.1

When the Naming Service is persistently launched, the Password dialog box is displayed at the same time as the missing font messages below:

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal--*-%d-*-*p-*-sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal--*-%d-*-*p-*-sun-fontspecific]
```

```
Font specified in font.properties not found [-urw-its zapfdingbats-medium-r-normal--*-%d-*-*p-*-sun-fontspecific]
```

The fonts specified in `font.properties` need to be found on the host system. Otherwise these messages are displayed.

Workarounds

- Customize the `font.properties` file for each machine.
- Install the SUNIWof font packages.